## **Brass Swing Check Valve**

## **Feature**

200# WOG Brass body Brass seat FNPT x FNPT Threaded ends (ASME B1.20.1-NPT) Horizontal "T" pattern


Pressure/ Temperature rating				
200# WOG	Temp. max. 450 °F			



## Material

	Part	Material	Specification		
1	Body	Brass	ASTM B124 C37700		
2	Retaining disc	Brass	ASTM B124 C37700		
3	Stem	Brass *	ASTM B124 C37700		
4	Bolt	Brass	ASTM B124 C37700		
5	Gasket	PTFE	PTFE		
6	Сар	Brass	ASTM B124 C37700		

<sup>\*</sup> Stainless steel stem for size 2 1/2" - 4"



## Dimension, Weight

Size	Т	A [in]	H [in]	<b>L</b> [in]	B [in]	C [in]	P [in]	Wt. [lb]
1/2"	½ - 14 NPT	2.22	1.39	1.26	0.96	0.61	0.51	0.45
3/4"	3⁄4 - 14 NPT	2.47	1.57	2.50	1.02	0.63	0.73	0.65
1"	1 - 11.5 NPT	3.03	1.81	1.77	1.14	0.75	0.94	1.02
11/4"	1¼ - 11.5 NPT	3.31	2.19	2.11	1.50	0.77	1.20	1.43
11/2"	1½ - 11.5 NPT	3.62	2.42	2.44	1.61	0.77	1.42	1.92
2"	2 - 11.5 NPT	4.21	2.81	2.95	1.48	0.79	1.77	2.71
21/2"	2½ - 8 NPT	5.63	3.48	3.74	1.81	1.06	2.24	5.81
3"	3 - 8 NPT	6.18	3.91	4.41	2.05	1.14	2.56	7.62
4"	4 - 8 NPT	7.44	4.51	5.51	2.40	1.20	3.58	12.14

