

ECO-VALVE

5014AB DZR Lead Free Brass PEX Ball Valve

Feature

400# WOG DZR lead free brass body F1960 full port Barb (F1960) x EzPress PEX end (ASTM F1960) Chrome plated ball Virgin PTFE seats Blow-out proof stem Double NBR O-ring packing CSA B125.14 AB1953, NSF/ANSI 61 & 372 certified





DZR Dezincification Resistant

Option with wing handle (5014ABW) available Extension stem available






Material

	Part	Material	Specification		
1	Body	DZR Lead Free Brass	ASTM B927 C27453		
2	End piece	DZR Lead Free Brass	ASTM B927 C27453		
3	Ball	DZR Lead Free Brass / Cr plated	ASTM B927 C27453		
4	Seat	PTFE	PTFE		
5	Stem	DZR Lead Free Brass	ASTM B927 C27453		
6	O-ring	NBR	NSF approved		
7	Handle	Steel / Dacromet [®] plated	ASTM A36		
8	Handle nut	Steel / Zn plated	ASTM A36		

Dimension, Weight

redwhitevalvecorp.com

	EzPress [in]	A [in]	H [in]	L [in]	P [in]	C [in]	Wt. [lb]
1⁄2"	0.638	2.62	1.38	3.19	0.39	0.87	0.26
3/4"	0.886	2.38	1.77	3.58	0.61	0.98	0.49
1"	1.138	4.05	1.93	3.58	0.81	1.06	0.75





WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive barm. For more information on to www.P65Warnings.ca.gov.

cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Drawings, photos and data are provided for information only and subject to change without notice. No part of this document may be reproduced, copied, modified or adapted, without the prior written consent of the copright owner, unless otherwise indicated. The Drinking Water Act has defined lead ree as having the average wetted surface ratio of the fixture to contain less than .25% of lead per volume. pg1/1 [200713]

© 2020 Red-White Valve Corp. All Rights Reserved