



PTFE THREAD SEAL TAPE (INDUSTRIAL)

Meets MIL Spec T-27730A

- For all industrial applications.
- Made from 100% virgin PTFE.
- No pigments, no additives.
- Exceeds MILSpec T-27730A.
- Temperature range of -450F to +550F.
- VOC's (Volatile Organic Compounds): Minimal. 1.5% or less
- May be used on all applications including water, oil, chemical, medical, and food processing where non-contamination standards are high.

60-10-260	1/2" x 260" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-262	1/2" x 520" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-264	1/2" x 1296" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-262	3/4" x 260" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-267	3/4" x 520" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-269	3/4" x 1296" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-270	1" x 260" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-271	1" x 520" STANDARD 0.4 DENSITY INDUSTRIAL GRADE
60-10-272	1" x 1296" STANDARD 0.4 DENSITY INDUSTRIAL GRADE

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**