

Better than it has to be[®] Since 1903





BENEFITS:

- » Improved Foam and Corrosion Prevention
- » Improved Oxidation Stability

MADE IN U.S.A.

» Promotes Smooth Shifting







AMALIE Mercon[®] V ATF is for use in Ford vehicle transmissions and transaxles. Especially formulated to exhibit better low-temperature flow and better shear-stability. AMALIE Mercon[®] V ATF meets Ford performance requirements of vehicles specifying Mercon[®] V ATF. AMALIE Mercon[®] V ATF is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese, and other manufactures from around the world specifying Mercon[®] V type transmission fluids.

Check owner's manual for specific recommendations.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Kinematic Viscosity @100°C, cSt	7.4
Kinematic Viscosity @40°C, cSt	
Viscosity Index	
Brookfield Viscosity, cP @ -40 (°C)	<13,000
Flash Point, °C (°F)	
Pour Point, °C (°F)	48 (-54)

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

APPLICATIONS

Mercon[®] V, Mercon[®]

*Always refer to your vehicles operating manual to select the correct grade oil for your transmission.

**Transmission fluids also applicable in power steering units; check owners' manual.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

AUTOMATIC TRANSMISSION FLUID

VISCOSITY	PACK SIZE	PART #
Mercon®V ATF	12-1 Quart	160-62856-56
	55 Gallon Drum	160-62853-05

The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.