

A carbon monoxide monitor continuously samples compressed breathing air to alert operators to the presence of harmful carbon monoxide (CO), an odorless, tasteless, colorless gas. The Barricade CO Monitor uses audio and visual alarms to notify operators when CO levels exceed the allowable level. The Barricade CO Monitor is a critical component of a respiratory program, as required by OSHA 29CFR 1910.134. Commonly used with supplied-air respirators for use in abrasive blasting, general cleaning, inspecting, and painting and coating applications.



## ENHANCED SAFETY

Carbon Monoxide is an odorless, tasteless, and colorless gas. The Barricade CO Monitor continuously samples the breathing air supplied to a respirator for the presence of carbon monoxide, triggering an alarm when the established allowable level is exceeded.

## APPLICATION VERSATILITY

The Barricade CO Monitor includes a locking power cord port equipped for 12-Volt DC or 120-Volt AC power input. The automatic locking feature on the plug reduces unintentional unplugging from the power source.

## COMMITMENT TO QUALITY

Our commitment to producing the highest quality products in the industry demands strict control over our raw materials and manufacturing processes. All components used in the manufacturing of Marco products adhere to strict process controls as specified by Allredi's Quality and Engineering team.



An Easy-View Window provides visibility to the displays without having to open the case. The flow gauge indicates active air sampling, LED lights show Barricade CO Monitor status, and the LCD display indicates the level of CO present in the air.



As your available power source changes, the Barricade CO Monitor can quickly and easily be adapted to 12-Volt DC or 120-Volt AC by simply changing out your power cord.



An optional magnetic-backed Remote Strobe Light & Alarm allows you the flexibility to stage the Barricade CO Monitor in a protected area, while placing the Remote Strobe Light & Alarm device closer to the workers.





## KEY FEATURES

- Easy-view window
- Operating status LED lights
- Manual Alarm Silencer
- 12-Volt DC or 120-Volt AC power source flexibility
- 105 dB audio alarm with visual alarms
- Rugged enclosure
- Remote Strobe Light & Alarm compatible

### Calibration Kit



The Calibration Kit includes Zero Gas, Span Gas, Calibration Hose and Fitting, Flow Regulator with Indicator Gauge, and Potentiometer Tool in a convenient storage case.

### Remote Strobe Light & Alarm



The Remote Strobe Light & Alarm can be placed up to 250 feet from the CO Monitor.

### 5 Ft. x 3/8" I.D. Supply Hose



A five foot, 3/8" I.D. supply hose is available for connecting to a Barricade 286 Airline Filter.

### Barricade 286 Airline Filter



The Barricade 286 Airline Filter includes filtration that catches and removes moisture, odors, organic vapors, and other particles from the air supply.



800.252.7848



SALES@ALLREDI-US.COM



WWW.ALLREDI-US.COM