



The Right Connection®

British Instantaneous Fittings from Dixon Fire

Features:

- polished brass finish
- meets BS336 specifications

Adapters

Configuration		Part #	Weight
Female	Female		
2½" BRIT	2½" NST (NH)	BID250F	3 lbs. 10 ozs.
2½" BRIT	2½" NPSH	BID250S	
2½" BRIT	2½" NPT	BID250T	
2½" BRIT	2½" BSP	BID250B	



British Instantaneous female x female threads

Configuration		Part #	Weight
Female	Male		
2½" BRIT	2½" NST (NH)	BIB250F	3 lbs. 5 ozs.
2½" BRIT	2½" NPSH	BIB250S	
2½" BRIT	2½" NPT	BIB250T	
2½" BRIT	2½" BSP	BIB250B	



British Instantaneous female x male threads

Configuration		Part #	Weight
Male	Female		
2½" BRIT	2½" NST (NH)	BIA250F	2 lbs. 9 ozs.
2½" BRIT	2½" NPSH	BIA250S	
2½" BRIT	2½" NPT	BIA250T	
2½" BRIT	2½" BSP	BIA250B	



British Instantaneous male x female threads

Configuration		Part #	Weight
Male	Male		
2½" BRIT	2½" NST (NH)	BIF250F	2 lbs. 5 ozs.
2½" BRIT	2½" NPSH	BIF250S	
2½" BRIT	2½" NPT	BIF250T	
2½" BRIT	2½" BSP	BIF250B	



British Instantaneous male x male threads

Plug

Size	Part #	Weight
2½"	BIDP250	1 lb. 13 ozs.



Cap

Size	Part #	Weight
2½"	BIDC250	3 lbs. 8 ozs.



Hose Shanks

Configuration	Part #	Weight
2½" MBI x 1½" hose shank	BIE150	2 lbs. 11 ozs.
2½" FBI x 1½" hose shank	BIC150	3 lbs. 12 ozs.



BIE150



BIC150

ph: 410.778.2008
fx: 410.778.4702

Dixon Fire
800 High Street • Chestertown, MD 21620
dixonvalve.com

ph: 877.712.6179
fx: 800.283.4966