

### Polyurethane Self-Storing Air Hose (fittings included)

**Features**

- Extremely flexible - resists kinking
- Impervious to abrasions, heat and oil
- Superior elasticity and coil memory
- Both ends swivel

Hose I.D.	Length	Male NPT	Working Pressure (PSI) @75°F	Polyurethane Part #
1/4"	10'	1/4"	125	PU1410
	15'	1/4"	125	PU1415
	25'	1/4"	125	PU1425
3/8"	15'	3/8"	115	PU3815
	20'	3/8"	115	PU3820
	25'	3/8"	115	PU3825
	50'	3/8"	115	PU3850
1/2"	15'	1/2"	115	PU1215 <sup>1</sup>



<sup>1</sup> Supplied without fittings for custom assemblies

#### Repair Kits

Size	Tubing Size		Type	Brass Part #
	I.D.	O.D.		
1/4"	1/4"	3/8"	swivel male	PSM0404
	3/8"	9/16"	swivel male	PSM0604

NOTE: Male NPT to size



### Polyurethane Air Hose with Strain Relief Fittings

**Application**

- Metal-working or wood-working operations, in which product shavings or sawdust often make it difficult to view the work surface

**Features**

- Male NPT
- Kinking with polyurethane resin
- Built-in industrial coupler blow gun
- Works with tool connected or disconnected

**Materials**

- Air hose: polyurethane
- Blow gun: brass and plated steel



Hose I.D.	Length	Male NPT	Working Pressure (PSI) @ 70°F (21°C)	Polyurethane Part #
1/4"	25'	1/4	120	PU1425-CBG

### Industrial Coupler Blow Gun

**Application**

- This convenient unit is perfect for metalworking or woodworking operations, in which product shavings or sawdust often make it difficult to view the work surface

**Features**

- Already on your hose and ready to use
- Easy push button trigger
- 1/4" Industrial with 1/4" female NPT
- Works with tool connected or disconnected
- Safety glasses or shield must be worn when using any blow gun
- 120 PSI maximum



**Materials**

- Blow gun: brass and plated steel



Female NPT	Part #
1/4"	CBG25