


### Hydraulic Adapters - 37° JIC

#### 90° Male Flare x Male NPTF Elbows

**Specifications**

- Reference SAE 070202
- Pressure rating at 70°F (21°C)



Male JIC 37° Flare	Male NPTF	PSI	Zinc Plated Steel Part #	316 Stainless Steel Part #
7/16"-20	1/8"-27	4500	2501-4-2	---
	1/4"-18	4500	2501-4-4	SS2501-4-4
	3/8"-18	4000	2501-4-6	---
9/16"-18	1/8"-27	4000	2501-6-2	---
	1/4"-18	4000	2501-6-4	---
	3/8"-18	4000	2501-6-6	SS2501-6-6
3/4"-16	1/2"-14	3000	2501-6-8	---
	1/4"-18	4000	2501-8-4	---
	3/8"-18	4000	2501-8-6	---
	1/2"-14	3000	2501-8-8	SS2501-8-8
7/8"-14	3/4"-14	2500	2501-8-12	---
	1/2"-14	3000	2501-10-8	---
	3/4"-14	2500	2501-10-12	---
1-1/16"-12	1/2"-14	3000	2501-10-12	---
	3/4"-14	2500	2501-12-8	---
	1"-11-1/2	2000	2501-12-12	SS2501-12-12
1-5/16"-12	1"-11-1/2	2000	2501-12-16	---
	3/4"-14	2500	2501-12-16	---
	1"-11-1/2	2000	2501-16-12	---
1-5/8"-12	1"-11-1/2	2000	2501-16-16	SS2501-16-16
	1-1/4"-11-1/2	1150	2501-20-16	---
1-7/8"-12	1-1/2"-11-1/2	1000	2501-20-20	---
2-1/2"-12	2"-11-1/2	1000	2501-24-24	---
			2501-32-32	---

#### 90° Female Swivel x Male NPTF Elbows

**Specification**

- Pressure rating at 70°F (21°C)



Female JIC 37° Swivel	Male NPTF	PSI	Zinc Plated Steel Part #
7/16"-20	1/8"-27	4500	6501-4-2
	1/4"-18	4500	6501-4-4
1/2"-20	1/8"-27	4000	6501-5-2
9/16"-18	1/4"-18	4000	6501-6-4
	3/8"-18	4000	6501-6-6
3/4"-16	3/8"-18	4000	6501-8-6
	1/2"-14	3000	6501-8-8
7/8"-14	1/2"-14	3000	6501-10-8
1-1/16"-12	3/4"-14	2500	6501-12-12
1-3/16"-12	3/4"-14	2500	6501-14-12
1-5/16"-12	1"-11-1/2	2000	6501-16-16
1-5/8"-12	1-1/4"-11-1/2	1150	6501-20-20
1-7/8"-12	1-1/2"-11-1/2	1000	6501-24-24
2-1/2"-12	2"-11-1/2	1000	6501-32-32

#### 45° Male Flare x Female Swivel Elbows

**Specifications**

- Reference SAE 070321
- Pressure rating at 70°F (21°C)



Male JIC 37°	Female JIC 37° Swivel	PSI	Zinc Plated Steel Part #
7/16"-20	7/16"-20	4500	6502-4
9/16"-18	9/16"-18	4000	6502-6
3/4"-16	3/4"-16	4000	6502-8
7/8"-14	7/8"-14	3000	6502-10
1 1/16"-12	1 1/16"-12	3000	6502-12
1 5/16"-12	1 5/16"-12	2500	6502-16
1-5/8"-12	1-5/8"-12	2000	6502-20

K