

59180J

1/4 Tie Wire Drive Anchor

UPC: 08593705445

UNSPSC: 31162107

Standard Qty: 100

Master Carton Qty: 600

Country of Origin: CHINA

1/4" x 1-1/4" Tie Wire Drive Anchor, Zinc Plated, 100/Jar



Product Attributes

Ultimate Load Capacities (3000 PSI Concrete)	1075 lbs Tension, 1310 lbs Shear
Type	Tie Wire Spike Anchor
Brand Name	Minerallac
Sub Brand	Cully
Material	Carbon Steel
Finish	Zinc Plating
Application	Designed for suspended ceilings the tie wire spike anchor is a one-piece vibration resistant anchor for use in concrete, block, or stone. The spike anchor is designed with an "s" shape at the working end of the anchor to create an expansion mechanism. No secondary tightening operation required.
Drill Size	1/4"
Tie Wire Hole	9/32
Anchor Size	1/4" x 1- 1/4"
Allowable Load Capacities (3000 PSI Concrete)	270 lbs Tension, 330 lbs Shear

Compliance Information

Buy America Act Compliant: No

Buy American Act Compliant: No

RoHS Compliant: Yes

UL Listed: No

UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293

Fax: 800-824-8942

www.minerallac.com

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.