

|              |                                    |
|--------------|------------------------------------|
| <b>96064</b> | <b>FIRE STOP CAULK 150+ 20.2oz</b> |
|--------------|------------------------------------|

UPC: 08593796064  
 UNSPSC: 46191503  
 Standard Qty: 1  
 Master Carton Qty: 12  
 Country of Origin: USA  
 Firestop Caulk 150+, 20.2 oz, 1ct Sausage Tube



| Product Attributes        |   | Compliance Information   |
|---------------------------|---|--|
| Brand Name                | Minerallac  | Buy America Act Compliant: No  |
| Sub Brand                 | Cully   | Buy American Act Compliant: No   |
| Type                      | Firestop Sealants   | RoHS Compliant: No   |
| Description               | General purpose fire rated sealant, acoustic sealant, and smoke seal for construction joints and through-penetrations. 150+ is a water based, non-sag caulking grade sealant that is easy to apply as well as retrofit.   | UL Listed: No  |
| Application               | Metacaulk 1000 can be used in interior applications as a general purpose fire rated sealant and smoke seal for construction joints, through penetrations and blank openings on both vertical and horizontal surfaces. Use Metacaulk 1000 to prevenet the spread of fire and smoke through joints in fire rated gypsum wallboard partitions, concrete block or concrete walls and/ or concrete or corrugated steel deck floor/ ceiling assemblies. | UL Code:   |
| Size                      | 20.2 oz foil sausage pack   | <b>Proposition 65</b>  |
| Characteristics/ Features | Water based, excellent freeze-thaw, flexible set, paintable, VOC compliant, safe and easy to use, STC rating 65   | This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation. |
|                           |   | <b>Minerallac Company</b>  |
|                           |   | Tel: 800-927-3293<br>Fax: 800-824-8942<br>www.minerallac.com   |

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.