

Pro-Flex™ Cap Fitting



PECAP2-Series

APPLICATION

The Pro-Poly™ Cap Fitting is used to terminate the end of a poly pipe for future use or leak testing.

INSTALLATION

Product installation and system testing shall be completed by a qualified installer in accordance with NFPA 54/ANSI Z223.1 (National Fuel Gas Code), National Gas & Propane Installation Code B149.1 (Canada), state/local codes and the Pro-Flex Installation/Training Guide.

MATERIALS

Nut and Main Body: Polypropylene

O-Ring: Nitrile

Spacer: Nylon

Grip Ring: Acetal

Stiffener: Acetal

SPECIFICATIONS

APPROVED GASES: **LP (PROPANE) & NATURAL GAS**

MAX WORKING PRESSURE: 80 PSIG

MAX TESTING PRESSURE: 120 PSIG

CODES, STANDARDS & LISTINGS:

Codes: NFPA 54, ICC Codes [IFGC, IRC, IPC, IMC], UPC, UMC

Standards: ASTM F1924-10218

Listings: IAPMO



DIMENSIONAL DATA:

Item Number	Qty per Box	Poly Pipe Size
PECAP2-12CTSC	6	1/2" CTS .625" x .090
PECAP2-34C	6	3/4" IPS SDR 11
PECAP2-01C	6	1" IPS SDR 11
PECAP2-0114C	1	1 1/4" IPS SDR 11
PECAP210-0114C	1	1 1/4" IPS SDR 10
PECAP2-015C	1	1 1/2" IPS SDR 11
PECAP2-02C	1	2" IPS SDR 11



Pro-Flex™
Traditional CSST

Pro-Flex LLC

FlakJacket™
Arc-Resistant CSST

www.proflexcsst.com

HearthMaster™
Gas Valves, Keys & Bars

1-877-798-6291

Pro-Poly™
Underground Gas Piping