



SERVICE METAL
Trust In Every Connection

MASTER DISTRIBUTOR OF
PIPE FITTINGS & VALVES

Common Nipples Lengths Nipples Weights and Packaging Inches / Pounds

STD/Schedule 40
(ASTM B687 UNS C23000 **Lead Free Brass***)
(PBE,TBE,TOE)



Size	Close Length	Weight per piece (lb)																
		Packing (Inner Box/Case)																
		Close	1-1/2	2	2-1/2	3	3-1/2	4	4-1/2	5	5-1/2	6	7	8	9	10	11	12
1/8	3/4	0.016	0.033	0.045	0.056	0.067	0.079	0.090	0.101	0.113	0.124	0.136	0.158	0.181	0.20	0.23	0.25	0.27
		25/600	25/600	25/600	25/600	25/600	25/600	25/600	25/400	25/400	25/400	25/400	25/200	25/200	25/200	25/150	25/150	25/150
1/4	7/8	0.035	0.061	0.060	0.081	0.102	0.123	0.144	0.165	0.186	0.21	0.23	0.27	0.31	0.35	0.40	0.44	0.48
		25/600	25/600	25/600	25/600	25/600	25/400	25/400	25/400	25/300	25/300	25/300	25/200	25/200	25/200	25/150	25/150	25/150
3/8	1	0.052	0.079	0.079	0.106	0.133	0.160	0.186	0.21	0.24	0.27	0.29	0.35	0.40		0.51	0.56	0.62
		25/600	25/600	25/600	25/400	25/400	25/300	25/300	25/300	25/200	25/200	25/200	25/200	25/150		25/100	25/100	25/100
1/2	1-1/8	0.082	0.078	0.116	0.154	0.192	0.23	0.27	0.30	0.34	0.38	0.42	0.49	0.57	0.65	0.72	0.80	0.87
		25/600	25/600	25/600	25/400	25/400	25/300	25/300	25/200	25/200	25/200	25/200	25/100	25/100	25/100	25/75	25/75	25/75
3/4	1-3/8	0.128	0.100	0.147	0.195	0.24	0.29	0.34	0.39	0.43	0.48	0.53	0.63	0.72	0.82	0.91	1.01	1.11
		25/400	25/400	25/300	25/300	25/200	25/200	25/150	25/150	25/100	25/100	25/100	25/75	25/75	25/75	25/50	25/50	25/50
1	1-1/2	0.160		0.23	0.29	0.36	0.43	0.50	0.56	0.63	0.70	0.76	0.90	1.03	1.17	1.30	1.44	1.57
		25/300		25/200	25/200	25/150	25/150	25/100	25/100	25/100	25/100	25/75	25/50	25/50	25/50	20/40	25/50	25/50
1-1/4	1-5/8	0.25		0.32	0.41	0.50	0.60	0.69	0.78	0.87	0.96	1.06	1.24	1.42	1.61	1.79	1.97	2.16
		25/150		25/150	25/150	25/100	25/100	25/100	25/75	25/75	25/75	25/50	15/50	15/30	15/50	-/40	-/40	-/30
1-1/2	1-3/4	0.31		0.37	0.47	0.58	0.68	0.78	0.89	0.99	1.10	1.20	1.41	1.62	1.83	2.04	2.25	2.46
		25/100		25/75	25/75	25/50	25/50	25/50	-/50	-/50	-/50	-/50	-/40	-/40	-/30	-/30	-/20	-/20
2	2	0.55			0.70	0.85	1.01	1.15	1.31	1.47	1.62	1.78	2.08	2.39	2.70	3.0	3.3	3.6
		25/75			25/50	-/50	-/40	-/40	-/40	-/40	-/30	-/30	-/20	-/20	-/20	-/20	-/15	-/15
2-1/2	2-1/2	1.09				1.33	1.57	1.82	2.06	2.30	2.54	2.79	3.3	3.8	4.2	4.7	5.2	5.7
		-/40				-/40	-/30	-/30	-/30	-/20	-/20	-/20	-/20	-/10	-/10	-/10	-/10	-/10
3	2-5/8	1.52				1.76	2.08	2.39	2.71	3.0	3.3	3.7	4.3	4.9	5.6	6.2	6.8	7.5
		-/30				-/20	-/15	-/15	-/15	-/15	-/15	-/10	-/7	-/7	-/7	-/5	-/5	-/5
3-1/2	2-3/4	2.09						3.0						6.7				10.0
		-/20						-/8						-/4				-/4
4	2-7/8	2.40						2.96	3.9	4.3	4.8	5.2	6.1	7.0	7.9	8.8	9.7	10.6
		-/20						-/10	-/8	-/8	-/8	-/8	-/4	-/4	-/4	-/4	-/4	-/4

Lead Free Brass* ASTM B687 UNS C23000
NPT Threads on all fittings conform to ASME B1.20.1

NSF/ANSI/CAN 61 Drinking Water System Components – Health Effects
NSF/ANSI/CAN 372 Drinking Water System Components – Lead Content

***Conforms with lead content requirements for lead-free plumbing as defined by the U.S. Safe Drinking Water Act. Certified <0.25 weighted average % lead.**