# Lead Free Vacuum Breaker Threaded Connection







### Features


- 3/4" hose connection
- Tamper-resistant breakaway screw
- Heavy brass construction
- POM internal components
- Wetted surfaces contain less than .25% lead content

## Approvals GLEAD FREE

- Truesdail Certified NSF/ANSI/CAN 61 & 372
- ANSI B1.20.7

### **Temperature and Pressure Ratings**

• 300 WOG - 150 PSI



### **Material Specifications**

| No.                   | Part       | Materials       |  |  |
|-----------------------|------------|-----------------|--|--|
| 1                     | Body       | Lead Free Brass |  |  |
| 2                     | Diaphragm* | Buna-N          |  |  |
| 3                     | Spring*    | Stainless Steel |  |  |
| 4                     | Set Screw  | Steel           |  |  |
| *Not shown in drawing |            |                 |  |  |

| Dimensions |      |      |      |  |  |
|------------|------|------|------|--|--|
| Part No.   | Size | Α    | В    |  |  |
| 203-204G   | 3/4" | 1.55 | 1.34 |  |  |



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.