# 5026AB

# DZR Lead Free Brass Full Port EzPress Hose End Ball Valve

### **Feature**

600# WOG
DZR lead free brass body
Full port
EzPress x Hose end
Male NH (ASME B1.20.7)
Chrome plated ball
Virgin PTFE seats
Adjustable packing
Blow-out proof stem
Drain cap with chain
MSS-SP-110
AB1953, NSF/ANSI 61 & 372 certified










### Meet BAA requirement

Pressure/ Temperature rating						
Valve body and stem						
600 psi from 15 °F to 160 °F	150 psi max. at 366 °F					
Press connections						
250 psi from 15 °F to 160 °F	150 psi max. at 250 °F					

#### Material

	Part	Material	Specification		
1	Body	DZR Lead Free Brass	ASTM B927 C27453		
2	End piece	ASTM B927 C27453			
3	Ball	Lead Free Brass / Cr plated	ASTM B927 C28500		
4	Seat	PTFE	PTFE		
5	Stem	Lead Free Brass	ASTM B927 C27450		
6	Packing ring	PTFE			
7	Packing nut	Brass	ASTM B124 C37700		
8	Handle	Steel / Geomet® plated	ASTM A36		
9	Nut	Steel / Zn plated	ASTM A36		
10	Valve info	-	-		
11	O-ring	EPDM Perox	NSF approved		
12	Cap gasket	EPDM Perox	NSF approved		
13 Drain cap + chain		Brass	ASTM B124 C37700		



## Dimension, Weight

	Size	Т	<b>A</b> [in]	L [in]	H [in]	<b>D</b> [in]	P [in]	C [in]	C1 [in]	Wt.
ľ	3/4"	¾ - 11.5NH	3.35	3.60	2.26	0.89	0.87	0.98	0.51	0.76

