



Materials/Finishes:	Plain Carbon Steel (275B)	Electro-Galvanized (275G)
	Hot-Dip Galvanized (275HDG)	T-304 Stainless Steel (275SS)*
	T-316 Stainless Steel (275SX)*	
Variants:	With Nonconductive Roll (275NCR)	
Max Temp:	275B = 400°F 275G = 350°F 275HDG = 350°F (excludes 275SS, SX and NCR)	
Service:	Designed for the support of pipe where longitudinal movement may occur due to expansion and contraction, and vertical adjustment is not necessary. May be bolted or welded to supporting member.	
Approvals:	Complies with Federal Specification WW-H-171-E (Type# 42), A-A-1192 A (Type# 41) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 41).	
Ordering:	Specify figure number, finish and roller size. Please remember to consider insulation thickness when sizing rollers	
Notes:	Mounting hardware not included. * <b>Not available in 3-1/2, 5, 7, 24 or 30.</b>	

HANGER SIZE	AXLE SIZE	B	C	D	E	F	WGT EACH (lbs)	MAX REC LOAD (lbs)
2	3/8	1-9/16	1-3/8	1-1/4	4-1/4	3/8	0.94	390
2-1/2	1/2	1-7/8	1-5/8	1-1/4	4-7/8	3/8	1.18	390
3	1/2	2-1/8	1-3/4	2	5-11/32	3/8	1.32	390
3-1/2	1/2	2-1/2	2	2	6-11/32	3/8	2.58	390
4	1/2	2-13/16	2-5/16	2	7-11/32	1/2	2.94	950
5	5/8	3-3/8	2-1/2	3	8-1/4	1/2	3.64	950
6	3/4	3-15/16	2-3/4	3-1/8	9-1/2	1/2	5.72	950
7	3/4	4-1/2	2-13/16	3-3/8	10	1/2	6.98	1350
8	7/8	5-1/8	3	3-3/8	12-1/4	5/8	8.16	1350
10	7/8	6-3/8	3-5/8	5-1/4	14-1/2	5/8	11.96	1730
12	7/8	7-1/2	4-1/8	5-1/2	16-1/4	5/8	15.86	2400
14	1-1/8	8-3/8	4-11/16	6-1/2	18	3/4	21.58	3130
16	1-1/4	9-3/8	5-3/8	8-1/4	21	3/4	34.50	3970
18	1-1/4	10-7/16	6	9-1/4	22-7/8	3/4	36.50	4200
20	1-1/4	11-5/8	6-1/2	10-1/4	25-1/4	3/4	45.00	4550
24	1-1/2	14	7-7/8	12-1/4	30	7/8	77.50	6160
30	1-3/4	17-15/16	8-3/4	15-3/8	34-13/16	7/8	110.00	7290

PROJECT INFORMATION			APPROVAL STAMP
Project:			Notes:
Address:			
Contractor:			
Engineer:			
Date:			
Approved	Approved as Noted	Not Approved	