



**ASTM Nominal Dimensions - Plumbing Tube**

Nominal Size	Actual OD	Type K	Wt/ft lbs	Type L	Wt/ft lbs	Type M	Wt/ft lbs	Type DWV	Wt/ft lbs
1/4"	.375	.035	.145	.030	.126	-		-	
3/8"	.500	.049	.269	.035	.198	.025	.145	-	
1/2"	.625	.049	.344	.040	.285	.028	.204	-	
5/8"	.750	.049	.418	.042	.362	-		-	
3/4"	.875	.065	.641	.045	.455	.032	.328	-	
1"	1.125	.065	.839	.050	.655	.035	.465	-	
1 1/4"	1.375	.065	1.04	.055	.884	.042	.682	.040	.650
1 1/2"	1.625	.072	1.36	.060	1.14	.049	.94	.042	.809
2"	2.125	.083	2.06	.070	1.75	.058	1.46	.042	1.07
2 1/2"	2.625	.095	2.93	.080	2.48	.065	2.03	-	
3"	3.125	.109	4.00	.090	3.33	.072	2.68	.045	1.69
3 1/2"	3.625	.120	5.12	.100	4.29	.083	3.58	-	
4"	4.125	.134	6.51	.110	5.38	.095	4.66	.058	2.87

**ASTM Nominal Dimensions**  
**Refrigeration Service Coils**

Actual OD	Wall Inches	Wt/ft
1/8"	.030	.0347
3/16"	.030	.0575
1/4"	.030	.0804
5/16"	.032	.109
3/8"	.032	.134
1/2"	.032	.182
5/8"	.035	.251
3/4"	.035	.305
7/8"	.045	.455
1 1/8"	.050	.655
1 3/8"	.055	.884
1 5/8"	.060	1.14

See Terms and Conditions for additional important product information  
 Issued: MAY 15, 2006