

VEP-Series Hydraulic Couplings

Features

- No-spill, flush face valve minimizes air inclusion during connection and spillage during disconnection
- Thread-to-connect design and dual valve system in the plug allow for connecting under pressure
- Design eliminates premature wear or brinelling commonly found with locking ball designs when subjected to high impulse pressures
- Zinc nickel plating provides superior corrosion resistance
- Interchangeable with Stucchi VEP, DNP PST 4/FSI, Holmbury HFT, Parker FET-Series, and Voswinkel FT-Series
- Contact Dixon® for pressure ratings and other technical information

Female Threaded Couplers

| Body Size | Threads | Steel Part # |
|-----------|----------------------|--------------|
| 1/4" | 1/4" - 18 NPTF | 2VEPF2 |
| | 1/4" - 19 BSPP | 2VEPBF2 |
| | 9/16" - 18 ORB | 2VEPOF3 |
| 3/8" | 3/8" - 18 NPTF | 3VEPF3 |
| | 3/8" - 19 BSPP | 3VEPBF3 |
| | 3/4" - 16 ORB | 3VEPOF4 |
| | 1/2" - 14 NPTF | 3VEPF4 |
| | 1/2" - 14 BSPP | 3VEPBF4 |
| 1/2" | 1/2" - 14 NPTF | 4VEPF4 |
| | 1/2" - 14 BSPP | 4VEPBF4 |
| | 3/4" - 16 ORB | 4VEPOF4 |
| | 7/8" - 14 ORB | 4VEPOF5 |
| | 3/4" - 14 NPTF | 4VEPF6 |
| | 3/4" - 14 BSPP | 4VEPBF6 |
| | 1-1/16" - 12 ORB | 4VEPOF6 |
| 3/4" | 3/4" - 14 NPTF | 6VEPF6 |
| | 3/4" - 14 BSPP | 6VEPBF6 |
| | 1-1/16" - 12 ORB | 6VEPOF6 |
| 1" | 1" - 11-1/2 NPTF | 8VEPF8 |
| | 1" - 11 BSPP | 8VEPBF8 |
| | 1-5/16" - 12 ORB | 8VEPOF8 |
| 1-1/4" | 1-1/4" - 11-1/2 NPTF | 10VEPF10 |
| | 1-1/4" - 11 BSPP | 10VEPBF10 |
| | 1-5/8" - 12 ORB | 10VEPOF10 |
| 1-1/2" | 1-1/2" - 11-1/2 NPTF | 12VEPF12 |
| | 1-1/2" - 11 BSPP | 12VEPBF12 |
| | 1-7/8" - 12 ORB | 12VEPOF12 |
| 2" | 2" - 11-1/2 NPTF | 16VEPF16 |
| | 2" - 11 BSPP | 16VEPBF16 |
| | 2-1/2" - 12 ORB | 16VEPOF16 |



316 Stainless Steel VEP-Series

| Body Size | Threads | Style | 316 Stainless Steel Part # |
|-----------|------------------|---------|----------------------------|
| 1" | 1" - 11-1/2 NPTF | coupler | 8VEPF8-SS |
| | | plug | VEP8F8-SS |