



Double Tapped Bushings



Inside Hex



Outside Hex

Part No.	Male	Female	Hex
4566	1" x 1/2"	1/2"	Outside
4567	1 1/4" x 3/8"	3/8"	Inside
4568	1 1/4" x 1/2"	1/2"	Inside
4569	1 1/4" x 3/4"	3/4"	Outside
4570	1 1/4" x 1"	1"	Outside
4571	1 1/2" x 3/8"	3/8"	Outside
4572	1 1/2" x 1/2"	1/2"	Inside
4573	1 1/2" x 3/4"	3/4"	Inside
4574	1 1/2" x 1"	1"	Outside
4575	1 1/2" x 1 1/4"	1 1/4"	Outside
4576	2" x 3/8"	3/8"	Inside
4577	2" x 1/2"	1/2"	Inside
4578	2" x 3/4"	3/4"	Inside
4579	2" x 1"	1"	Inside
4580	2" x 1 1/4"	1 1/4"	Outside
4581	2" x 1 1/2"	1 1/2"	Outside
4584	2 1/2" x 1 1/4"	1 1/4"	Inside

Part No.	Male	Female	Hex
4585	2 1/2" x 1 1/2"	1 1/2"	Inside
4586	2 1/2" x 2"	2"	Outside
4588	3" x 1"	1"	Inside
4589	3" x 1 1/4"	1 1/4"	Inside
4590	3" x 1 1/2"	1 1/2"	Inside
4591	3" x 2"	2"	Inside
4592	3" x 2 1/2"	2 1/2"	Inside
4596	3 1/2" x 1 1/2"	1 1/2"	Inside
4597	3 1/2" x 2"	2"	Inside
4599	3 1/2" x 3"	3"	Outside
4600	4" x 1"	1"	Inside
46001	4" x 1 1/4"	1 1/4"	Inside
4602	4" x 1 1/2"	1 1/2"	Inside
4603	4" x 2"	2"	Inside
4604	4" x 2 1/2"	2 1/2"	Outside
4605	4" x 3"	3"	Inside
4609	6" x 4"	4"	Inside

*** Double tapped full NPT female threads**

*** Rugged design has solid hexes for secure wrench grip**

*** Can be used as reducing bushings for continuous piping**