



Materials/Finishes:	Plain Carbon Steel (820B)	Electro-Galvanized (820G)
	Hot-Dip Galvanized (820HDG)	T-304 Stainless Steel (820SS)
	T-316 Stainless Steel (820SX)	
Variants:	N/A	
Service:	Recommended for the suspension of hanger rod for support of light loads up to 750 lbs. Rod can be suspended at any point along the length of the bracket, thus providing horizontal adjustment, using figure #820C clip which consists of two steel plates joined by a bolt and nut in one end.	
Approvals:	Fig. 820 complies with Federal Specification WW-H-171-E (Type# 32), A-A-1192 A (Type# 31) and Manufacturers' Standardization Society MSS SP 58 and SP 69 (Type# 31).	
Ordering:	Specify figure number, finish and size number	
Notes:	Piping suspended from FIG. 820C clip shall not exceed 3-1/2" in diameter. Side clip (FIG. 820C) to be ordered separately. Fig. 820C side clip is only available in HDG, T-304 and T-316 Stainless Steel.	



FIG. 820							
BRACKET SIZE	B	C-C	HOLES H	L	MATERIAL SIZE	WGT EACH (lbs)	MAX REC LOAD (lbs)
1	8	6-1/2	13/16	9	2 x 3/8	4.20	750
2	12	10-1/2	13/16	13	2 x 3/8	6.50	750
3	18	16-1/2	13/16	19	2 x 3/8	9.40	750

FIG. 820C			
CLIP NUMBER	PIPE SIZE	ROD SIZE A	WGT EACH (lbs)
1	3/4 - 2	3/8	0.80
2	2-1/2 - 3-1/2	1/2	1.24

PROJECT INFORMATION	APPROVAL STAMP
Project:	Notes:
Address:	
Contractor:	
Engineer:	
Date:	
Approved Approved as Noted Not Approved	