



Materials/Finishes	Plain Carbon Steel (95B)	Electro-Galvanized (95G)
	Hot-Dip Galvanized (95HDG)	T-304 Stainless Steel (95SS)
	T-316 Stainless Steel (95SX)	
Variants:	N/A	
Service:	Designed for supporting horizontal or vertical pipe lines at a fixed distance from wall or floor. This clamp can be furnished with "B" dimensions to suit field conditions.	
Approvals:	N/A	
Ordering:	Specify figure number, pipe type, finish and pipe size	
Notes:	Available in IPS (95) and Ductile Iron Pipe (95DIP) Sizes. Custom B dimension available. If clamp is being installed vertically, please contact factory for load ratings.	



PIPE SIZE	IPS OD	BOLT	B	A	C	D	WGT EACH (lbs)	* MAX REC LOAD (lbs)
1/2	0.84	3/8	2-9/16	8-3/4	7-3/16	7/16	1.51	200
3/4	1.050	3/8	2-5/8	8-7/8	7-3/8	7/16	1.62	200
1	1.315	3/8	2-5/8	9-1/8	7-5/8	7/16	1.70	200
1-1/4	1.660	3/8	2-13/16	9-1/2	8	7/16	1.75	200
1-1/2	1.900	3/8	2-15/16	9-5/8	8-1/16	7/16	1.82	200
2	2.375	3/8	3-3/16	10-3/4	9-3/8	7/16	2.07	410
2-1/2	2.875	3/8	3-7/16	11-5/8	10-1/4	7/16	2.24	410
3	3.500	3/8	3-3/4	12-3/4	11	7/16	2.52	410
3-1/2	4.000	3/8	4	13	11-1/4	7/16	2.64	410
4	4.500	1/2	4-1/4	13-1/2	11-1/2	9/16	3.61	600
5	5.563	1/2	4-3/4	15-3/8	13-3/8	9/16	4.00	600
6	6.625	1/2	5-5/16	16-3/8	14-1/2	9/16	6.51	850
8	8.625	1/2	6-5/16	19-1/4	17-1/4	9/16	7.92	850
10	10.75	3/4	7-3/4	25	23-1/8	13/16	20.03	900
12	12.75	3/4	8-3/4	27	25	13/16	23.24	900

* Stated load ratings are for horizontal installations only

PROJECT INFORMATION	APPROVAL STAMP
Project:	Notes:
Address:	
Contractor:	
Engineer:	
Date:	
Approved Approved as Noted Not Approved	