

PLASTIC ONE PIECE (Floor/Ceiling) WALL PLATES SPLIT FOR RETROFIT



CHROME PLATED



WHITE



BRASS PLATED

- Tough, durable plastic
- Non-breakable
- 100 % Rust Proof
- Interior/Exterior Use
- 200°F Max Temperature

Simply Bend Open...



...and Snap Closed!

SIZE	Chrome Plated	White	Brass Plated	I.D.	O.D.
3/8" IPS & 1/2" CPS	4525301	4525401	4525501	0.68"	2.50"
1/2" IPS & 3/4" CPS	4525100	4525200	4525130	0.88"	2.75"
3/4" IPS	4525101	4525200	4525131	1.06"	2.94"
1" IPS	4525102	4525202	4525132	1.33"	3.17"
1" CPS	4525302	4525402	4525502	1.20"	3.00"
1-1/4" IPS & 1-1/2" CPS	4525103	4525203	4525133	1.68"	3.54"
1-1/4" CPS	4525303	4525403	4525503	1.40"	3.25"
1-1/2" IPS	4525104	4525204	4525134	1.90"	3.83"

SIZE	Chrome Plated	White	Brass Plated	I.D.	O.D.
2" IPS	4525105	4525205	4525135	2.40"	4.38"
2" CPS	4525304				
2-1/2" IPS	4525106	4525206	4525136	2.93"	5.22"
3" IPS	4525107	4525207	4525137	3.57"	5.79"
4" IPS	4525108	4525208	4525138	4.52"	6.86"
5" IPS	4525109	4525209	4525139	5.67"	8.63"
6" IPS	4525110	4525210	4525140	6.50"	9.75"
8" IPS	4525111	4525211	4525141	8.56"	12.88"

Installation

The plastic wall plates may be installed by two methods.

1. Place the wall plate over the pipe while the pipe is being installed.
2. Split the wall plate at the area on the back of the wall plates that has been molded to break apart.
 Carefully bend the wall plate at this weakened area until fully separated.
 Then carefully twist the wall plate open just enough to be placed around the pipe.
 Allow the two ends of the separated wall plate to "spring" back into shape.
 Slide the wall plate up against the base material to finish the installation.

These wall plates should not be painted. Certain chemicals contained in paint may cause the wall plates to deteriorate.

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	